FIG. 1



FIG. 2



FIG. 3

PATENT PENDING



TOLERANCES

UNLESS OTHERWISE STATED

NOTE: PULLEY IS SAME AS ALTERNATE DESIGN 1, WITH THE EXCEPTION OF ADDED PARTS SHOWN.

MAX PD = 7.56
MIN PD = 4.25
SPECIAL A-SYMMETRICAL BELT

USED ON

SPEED SELECTOR INC.

TITLE CONTROL PULLEY
WITH WEIGHT ASSISTED VENTING
COMPUTER NO. P99049BE

FULL

DWG NO. P99049BE

Design #2



P99049
(conceived 6/28/00)

FIG 4

Design #3



Fig 5

Control Pulley
USING V-Belt
SEW

99049

Forest SET25760

Design #4



FIG 7A



FIG 7B

Stationary Double-Acting Cylinder, using V-Belt

SEW



FIG 7C

sew



Fig 8

SEW

Non-Rotating
linear electric motor





FIG 9



FIG 10


OTHER INPUTS FROM ACCESSORIES
28
27
RESERVOIR
PUMP
22
20
26
25
CONTROL LOGIC
ACTUATOR
CONTROL. VALVE
40
42
41
36
33
60
70
32
PULLEY A
19
60

FIG 11


OTHER INPUTS FROM ACCESSORIES
28
27
22
RESERVOIR
PUMP
20
26
CONTROL LOGIC
ACTUATOR
CONTROL VALVE
25
40
42
41
36
33
60
70
PULLEY A
19
39
60

FIG 12

FIG.13



FIG. 14

SPRING-ASSISTED VENTING



FIG. 15